## Premier<sup>™</sup> Retaining Wall Blocks





- Easy to handle for increased efficiencies in the field
- No cumbersome/expensive pins or clips
- Capable of tight radius turns
- Significant freight advantages, more sq. ft. per truckload







The 4 x  $2^{n}$  anchor bar on the underside of Premier 8 creates an automatic  $1^{n}$  ( $7^{\circ}$ ) setback with the highest shear resistance in the industry. Manufactured in accordance with ASTM C1372.

Block	Size	Face Area	Weight	Units/Layer	Layers	Units/Pallet	Pallet Weight
Premier 8	18 x 12 x 8" H	1 sq. ft.	54 lbs.	9	5	45 (45 sq. ft.)	2,480 lbs.
Premier 8 Corner	18 x 9 x 8" H	1 sq. ft.	105 lbs.	8	5	40 (40 sq. ft.)	4,250 lbs.
Premier 6	18 x 12 x 6" H	.75 sq. ft.	42 lbs.	9	6	54 (40.5 sq. ft.)	2,318 lbs.
Premier 6 Corner	16 x 8 x 6" H	.67 sq. ft.	63 lbs.	15	6	90 (60.3 sq. ft.)	5,720 lbs.
4" Straight Cap	16 x 10.5 x 4" H	.50 sq. ft.	59 lbs.	8	10	80 (120 LF)	4,770 lbs.
3" Universal Cap	16/12 x 11.5 x 3" H	.34 sq. ft.	37 lbs.	9	8	72 (84 LF)	2,714 lbs.



## Hi-Way Concrete Products, Inc.

2746 Cranberry Hwy, Wareham, MA 02571 656 State Rd, North Dartmouth, MA 02747 www.hiwayconcrete.com Phone: (508) 295-0834 Phone: (508) 997-8355

©Copyright 2024. All Rights Reserved. All trademarks and registered trademarks are the property of their respective owners. Rockwood Retaining Walls products are made worldwide under license from Rockwood Retaining Walls, Inc. US and international patents issued and pending. The information presented here has been prepared for the benefit of customers interested in Hi-Way Concrete Products Inc., it was reviewed carefully prior to publication. Hi-Way Concrete Products Inc. assumes no liability for its accuracy or completeness. Final determination of the suitability of any information or material for the use contemplated, or for its manner of use, is the sole responsibility of the user. 524